

**Manual sealless steel strapping tool with MicroLock™**

---

**Characteristics**

---

Strapping qualities:	Uniflex and Ultraflex max. 1100 N/mm <sup>2</sup> / 160'000 psi
Strapping dimensions:	widths 9.5 – 20.0 mm / <sup>3</sup> / <sub>8</sub> – <sup>3</sup> / <sub>4</sub> "
	thicknesses 0.38 – 0.63 mm / .015 – .025"
Weights:	4.45 kg / 9.8 lbs Normal-version
	4.7 kg / 10.4 lbs TW-version
Sealless joint:	Fromm MicroLock™
Average seal strength:	approx. 80 %
TW-version available:	Torque wrench tensioning system
Suspension (Optional):	Suspension for vertical and horizontal applications; has to be ordered separately
	Handle for horizontal applications; has to be ordered separately

**Advantages**

---

- The MicroLock™ sealless system guarantees a maximum of security of the sealless steel strapping joint against unlocking
- The tool can handle regular duty and high tensile steel strapping
- The tool can handle steel strapping up to a thickness of 0.64 mm / .025"
- Thanks to the special tensioning system (free wheeling) no loss of strap tension
- The sealing mechanism is completely closed
- The adjustment of the cutting and sealing depth is simple
- The feed wheel and the die and cutter support are easy to change

**Chart of types model A337**

Item No.	Model	Width		Thicknesses		Quality
		mm	inch	mm	inch	
13.1850	A337/9.5/0.38-0.50/TW/UNI	9.5	3/8"	0.38-0.50	.015-.020	Uniflex
13.1852	A337/9.5/0.38-0.50/ULT	9.5	3/8"	0.38-0.50	.015-.020	Ultraflex
13.1860	A337/10/0.38-0.50/TW/UNI	10		0.38-0.50	.015-.020	Uniflex
13.1862	A337/10/0.38-0.50/ULT	10		0.38-0.50	.015-.020	Ultraflex
13.1870	A337/12.7/0.38-0.50/TW/UNI	12.7	1/2"	0.38-0.50	.015-.020	Uniflex
13.1872	A337/12.7/0.51-0.63/TW/UNI	12.7	1/2"	0.51-0.63	.021-.025	Uniflex
13.1874	A337/12.7/0.38-0.50/ULT	12.7	1/2"	0.38-0.50	.015-.020	Ultraflex
13.1876	A337/12.7/0.51-0.63/ULT	12.7	1/2"	0.51-0.63	.021-.025	Ultraflex
13.1880	A337/13/0.38-0.50/TW/UNI	13		0.38-0.50	.015-.020	Uniflex
13.1882	A337/13/0.51-0.63/TW/UNI	13		0.51-0.63	.021-.025	Uniflex
13.1884	A337/13/0.38-0.50/ULT	13		0.38-0.50	.015-.020	Ultraflex
13.1886	A337/13/0.51-0.63/ULT	13		0.51-0.63	.021-.025	Ultraflex
13.1890	A337/16/0.38-0.50/TW/UNI	16	5/8"	0.38-0.50	.015-.020	Uniflex
13.1892	A337/16/0.51-0.63/TW/UNI	16	5/8"	0.51-0.63	.021-.025	Uniflex
13.1894	A337/16/0.38-0.50/ULT	16	5/8"	0.38-0.50	.015-.020	Ultraflex
13.1896	A337/16/0.51-0.63/ULT	16	5/8"	0.51-0.63	.021-.025	Ultraflex
13.1910	A337/19/0.38-0.50/TW/UNI	19	3/4"	0.38-0.50	.015-.020	Uniflex
13.1912	A337/19/0.51-0.63/TW/UNI	19	3/4"	0.51-0.63	.021-.025	Uniflex
13.1914	A337/19/0.38-0.50/ULT	19	3/4"	0.38-0.50	.015-.020	Ultraflex
13.1916	A337/19/0.51-0.63/ULT	19	3/4"	0.51-0.63	.021-.025	Ultraflex
13.1920	A337/20/0.38-0.50/TW/UNI	20		0.38-0.50	.015-.020	Uniflex
13.1922	A337/20/0.51-0.63/TW/UNI	20		0.51-0.63	.021-.025	Uniflex
13.1924	A337/20/0.38-0.50/ULT	20		0.38-0.50	.015-.020	Ultraflex
13.1926	A337/20/0.51-0.63/ULT	20		0.51-0.63	.021-.025	Ultraflex

Uniflex = Regular duty strapping max. 850 N/mm<sup>2</sup>/ 123'000 psi  
 Ultraflex = High tensile strapping max. 1100 N/mm<sup>2</sup>/ 160'000 psi

**Chart of types model A337 with torque wrench tensioning system**

Item No.	Model	Width		Thicknesses		Quality
		mm	inch	mm	inch	
13.1851	A337/9.5/0.38-0.50/TW/UNI	9.5	3/8"	0.38-0.50	.015-.020	Uniflex
13.1853	A337/9.5/0.38-0.50/TW/ULT	9.5	3/8"	0.38-0.50	.015-.020	Ultraflex
13.1861	A337/10/0.38-0.50/TW/UNI	10		0.38-0.50	.015-.020	Uniflex
13.1863	A337/10/0.38-0.50/TW/ULT	10		0.38-0.50	.015-.020	Ultraflex
13.1871	A337/12.7/0.38-0.50/TW/UNI	12.7	1/2"	0.38-0.50	.015-.020	Uniflex
13.1873	A337/12.7/0.51-0.63/TW/UNI	12.7	1/2"	0.51-0.63	.021-.025	Uniflex
13.1875	A337/12.7/0.38-0.50/TW/ULT	12.7	1/2"	0.38-0.50	.015-.020	Ultraflex
13.1877	A337/12.7/0.51-0.63/TW/ULT	12.7	1/2"	0.51-0.63	.021-.025	Ultraflex
13.1881	A337/13/0.38-0.50/TW/UNI	13		0.38-0.50	.015-.020	Uniflex
13.1883	A337/13/0.51-0.63/TW/UNI	13		0.51-0.63	.021-.025	Uniflex
13.1885	A337/13/0.38-0.50/TW/ULT	13		0.38-0.50	.015-.020	Ultraflex
13.1887	A337/13/0.51-0.63/TW/ULT	13		0.51-0.63	.021-.025	Ultraflex
13.1891	A337/16/0.38-0.50/TW/UNI	16	5/8"	0.38-0.50	.015-.020	Uniflex
13.1893	A337/16/0.51-0.63/TW/UNI	16	5/8"	0.51-0.63	.021-.025	Uniflex
13.1895	A337/16/0.38-0.50/TW/ULT	16	5/8"	0.38-0.50	.015-.020	Ultraflex
13.1897	A337/16/0.51-0.63/TW/ULT	16	5/8"	0.51-0.63	.021-.025	Ultraflex
13.1911	A337/19/0.38-0.50/TW/UNI	19	3/4"	0.38-0.50	.015-.020	Uniflex
13.1913	A337/19/0.51-0.63/TW/UNI	19	3/4"	0.51-0.63	.021-.025	Uniflex
13.1915	A337/19/0.38-0.50/TW/ULT	19	3/4"	0.38-0.50	.015-.020	Ultraflex
13.1917	A337/19/0.51-0.63/TW/ULT	19	3/4"	0.51-0.63	.021-.025	Ultraflex
13.1921	A337/20/0.38-0.50/TW/UNI	20		0.38-0.50	.015-.020	Uniflex
13.1923	A337/20/0.51-0.63/TW/UNI	20		0.51-0.63	.021-.025	Uniflex
13.1925	A337/20/0.38-0.50/TW/ULT	20		0.38-0.50	.015-.020	Ultraflex
13.1927	A337/20/0.51-0.63/TW/ULT	20		0.51-0.63	.021-.025	Ultraflex

TW = Torque wrench tensioning system

Uniflex = Regular duty strapping max. 850 N/mm<sup>2</sup> / 123'000 psi

Ultraflex = High tensile strapping max. 1100 N/mm<sup>2</sup> / 160'000 psi

**Accessories**

- A33.0121 Suspension for vertical and horizontal applications  
 A33.0122 Handle for horizontal applications